

ATF Dexron II

Product Description:

ATF Dexron II is formulated from highly refined paraffinic base oils with additive package designed to inhibit oxidation and offer load carrying anti-wear protection. ATF Dexron II fluids give high VI, low pour point, good corrosion and foaming resistance and are modified to create the particular dynamic frictional properties required.

Benefits:

- Constant frictional performance
- Good anti-wear characteristics
- Suitable for most power steering systems

Meets the requirements of:	
Ford	Mercon
GM	Dexron II, Dexron IID
MB	236.5, 236.6
Caterpillar	TO-2
Allison	C-4
ZF	TE-ML 09, 11A, 14A

Application:

ATF Dexron II is suitable for use in most automatic transmissions, torque converters, power steering units and hydraulic pumps as a service fill and top up fluid.

Typical Test Data:

Specific Gravity @ 15.5°C	0.888
Kinematic Viscosity @ 100°C (cSt)	7.86
Kinematic Viscosity @ 40°C (cSt)	44.77
Viscosity Index	147
Flash Point (°C)	229
Colour	Red

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our

recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfuels.co.uk>