

ATF Dexron III

Product Description:

ATF Dexron III is a multi-purpose automatic transmission fluid for commercial and passenger car gearboxes meeting a very wide range of specifications. The automatic transmission is one of the most complicated mechanisms in modern automotive engineering and consequently requires complex fluids for efficient operation. ATF Dexron III is manufactured from high quality solvent refined base oils with specially selected additives and friction modifiers to produce a lubricant with outstanding durability. It demonstrates excellent frictional stability and offers extended fluid life even when under the most severe conditions.

Benefits:

-
- Constant frictional performance
- Oxidation stability
- High temperature operation stability
- Wear protection
- Low temperature fluidity
- Seal compatibility
- Smooth operation of power transmission and power steering systems

Meets the requirements of:	
Ford	Mercon V
GM	Dexron III, Dexron IID
MAN	339F, 339
MB	236.1
Caterpillar	TO-2
Allison	C-4
ZF	TE-ML 03D, 04D, 09, 14A

Application:

ATF Dexron III is recommended for automatic transmissions and power steering units in cars, vans, trucks, buses, agricultural and industrial machines where the following specifications are required. This product should be avoided where Ford M2C33-G/F or ATF 33 is specified.

Typical Test Data:

Specific Gravity @ 15.5°C	0.876
Kinematic Viscosity @ 100°C (cSt)	8.00
Kinematic Viscosity @ 40°C (cSt)	36.2
Copper Corrosion	Nil
Flash Point (°C)	210
Colour	Red

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfueoils.co.uk>