

**SAFETY DATA SHEET
R250 BARRIER CREAM**



1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME R250 BARRIER CREAM

SUPPLIER Tygris Industrial
Unit 31 Kyle Road Industrial Estate
Irvine
KA12 8LE
01294 311066
technical@tygrisindustrial.com

2 HAZARDS IDENTIFICATION

Extremely flammable
CLASSIFICATION (1999/45) F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content % | Classification (67/548/EEC) |
|----------------------------------|-----------|------------|-----------|-----------------------------|
| ALCOHOL ETHOXYLATE | | 68439-45-2 | 1-5% | Xn;R22. Xi;R41. |
| BUTANE | 203-448-7 | 106-97-8 | 1-5% | F+;R12 |
| ISOBUTANE | 200-857-2 | 75-28-5 | < 1% | F+;R12 |
| PROPANE | 200-827-9 | 74-98-6 | 1-5% | F+;R12 |
| TRIETHANOLAMINE (COSMETIC GRADE) | 203-049-8 | 102-71-6 | 1-5% | Xi;R36/38. |

The Full Text for all R-Phrases is Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

R250 BARRIER CREAM

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|-----------|-----|--------------|--------------|---------------|--------------|-------|
| BUTANE | WEL | 600 ppm | 1450 mg/m3 | 750 ppm | 1810 mg/m3 | |
| ISOBUTANE | WEL | 800 ppm | | 800 ppm | | |
| PROPANE | | Asphyxiating | Asphyxiating | Asphyxiating | Asphyxiating | |

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-------------------------------|-------------------|
| APPEARANCE | Aerosol |
| COLOUR | White |
| ODOUR | Characteristic |
| SOLUBILITY | Soluble in water. |
| FLAMMABILITY LIMIT - LOWER(%) | 0.8 |
| FLAMMABILITY LIMIT - UPPER(%) | 9.0 |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

R250 BARRIER CREAM

INHALATION

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

INGESTION

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

SKIN CONTACT

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritating to eyes. May cause chemical eye burns.

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



| | |
|-------------------------|----------------------|
| PROPER SHIPPING NAME | AEROSOLS (TRICLOSAN) |
| UN NO. ROAD | 1950 |
| ADR CLASS NO. | 2 |
| ADR CLASS | Class 2: Gases |
| ADR PACK GROUP | N/A |
| TUNNEL RESTRICTION CODE | (D) |
| ADR LABEL NO. | 2.1 |
| UN NO. SEA | 1950 |
| IMDG CLASS | 2.1 |
| IMDG PACK GR. | N/A |
| EMS | F-D, S-U |
| UN NO. AIR | 1950 |
| AIR CLASS | 2.1 |
| AIR PACK GR. | N/A |

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable

RISK PHRASES

R12 Extremely flammable.

SAFETY PHRASES

S2 Keep out of the reach of children.

S16 Keep away from sources of ignition - No smoking.

R250 BARRIER CREAM

S23

Do not breathe vapour/spray.

S51

Use only in well-ventilated areas.

UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 11/07/2011

REV. NO./REPL. SDS GENERATED 6

RISK PHRASES IN FULL

| | |
|--------|---------------------------------|
| R12 | Extremely flammable. |
| R22 | Harmful if swallowed. |
| R36/38 | Irritating to eyes and skin. |
| R41 | Risk of serious damage to eyes. |

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.