



Multipurpose EP2

A premium quality multi-purpose grease for use in all anti-friction and plain bearings subjected to high load conditions. Used extensively for applications throughout industry and the automotive sector.

FEATURES:

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile multipurpose grease

METHOD OF APPLICATION

Multipurpose EP2 can be applied manually, or by using a standard grease gun (400gm cartridges available), or via a central lubricating system designed for and capable of pumping an NLGI No.2 grease; consult a qualified centralised lubrication systems engineer before installation. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to overlubricate and apply the quantity of grease recommended by the bearing manufacturer.

Properties	Specification	
Appearance	-	Smooth grease
Colour	-	Dark Brown
NLGI classification	-	2
Thickener	-	Lithium Soap
Base oil	-	Refined mineral oil
Worked penetration	IP50	265-295
Dropping point (°C)	IP132	185 min
Oil separation (%)	IP121	5 max
Copper corrosion	IP112	Pass
Resistance to corrosion Emcor (a)	IP 220	0:0
Water washout @ 39°C %	ASTM D1264	3
Four Ball Weld Load (kgs)	IP 239	315
Operating temperature range	-	-20°C to 140°C

The information above is believed to be accurate and given in good faith but without warranty. It is the users responsibility to determine the suitability of the product.

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety

data sheet in conformity with the legislation now current in the EC is available from
<http://www.fordfuels.co.uk>