



Premium Engine Oil 15W-40 CI-4

Mineral oil based heavy duty diesel engine oil.

Product Description:

Premium Engine Oil 15W-40 CI-4 is a high performance heavy duty diesel engine oil formulated to meet the severe lubrication requirements demanded by many commercial vehicle manufacturers.

Premium Engine Oil 15W-40 is a blend of solvent refined base oils, viscosity index improvers, pour point depressants and one of the most innovative additive systems to be developed in the last few years.

Meets the requirements of:	
API	CI-4/SL
ACEA	E7, A3/B3/B4
Mercedes Benz	228.3, 229.1
Cummins	CES 20078 CES 20071/72/76/77
MAN	M 3275
MTU	Type 2
Mack	EO-N EO-M+
Volvo	VDS-3
Renault	RVI RLD-2
Global	DHD-1
ZF	TE-ML 04C / 07C
Caterpillar	ECF-2
Allison	C4
Detroit Diesel	DDC 93K215
JASO	DH-1
Deutz	DQC III-10

Benefits:

- Meets the requirements of Volvo
- Meets the requirements of by Mack
- Meets the requirements of by Renault
- Meets the requirements of by Cummins
- Offers improved wear protection and soot handling properties
- Meets a very broad range of OEM specifications
- Ideal choice for mixed fleet long haul vehicles

Application:

Premium Engine Oil 15W-40 CI-4 is the first choice for a wide variety of European trucks and buses used for inter-city or long haul applications where an oil needing to satisfy the requirements of Euro 4 and certain Euro 5 engines is called for.

Premium Engine Oil 15W-40 CI-4 is at the forefront of heavy duty diesel engine oil technology, meeting API CI-4/SL and ACEA E7. Premium Engine Oil 15W-40 CI-4 is additionally suited to offhighway applications where piston cleanliness, oxidation resistance and wear protection are equally valued.

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from

<http://www.fordfueloils.co.uk>

Specific Gravity @ 15.5°C	0.887
Kinematic Viscosity @ 100°C (cSt)	14.39
Kinematic Viscosity @ 40°C (cSt)	106.02
Viscosity Index	139
TBN (mg KOH/g)	10.71
Pour Point (°C)	-31
Flash Point (°C)	210