



SUTO 10W-30 (Super Universal Tractor Oil)

Mineral oil based super universal tractor oil.

Product Description:

Lubricants Direct SUTO 10W-30 is an advanced high performance universal oil designed for use in the latest agricultural machinery. It is also recommended for a number of other off highway equipment including construction, demolition and excavation where any of the specifications below and a SAE 10W-30 viscosity grade are called for. SUTO 10W-30 is formulated using highly refined mineral base stocks together with state of the art additives which provide the ultimate protection against wear and corrosion and help eliminate wet brake noise and chatter.

Benefits:

- Meets the specification by Massey Ferguson
- Exceptional wear protection
- Enhanced anti-squawk properties providing superior wet brake performance
- Improved low temperature stability
- Meets a variety of OEM requirements
- Suitable for a wide range of off highway machinery requirements
- High API diesel specification

Application:

SUTO 10W-30 is suitable for use in naturally aspirated and turbocharged diesel and petrol engines, transmissions, hydraulic systems, final drives, wet brakes and oil immersed clutches.

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfueloils.co.uk>



SUTO Specs	
John Deere	J27
Massey Ferguson	MS1145
New Holland	NH 030C
Ford	ESN-M2C159-B/C
ZF	TE-ML 03A, 06B, 07B, 07D

UTTO Specs	
John Deere	J20C
Massey Ferguson	M1145
Ford	M2C134-D, M2C86-B
New Holland	NH 420A, NH 410B
Case New Holland	MAT 3525

Gear & Transmission Specs	
API	GL-4
Allision	C-4
Caterpillar	TO-2
Afnor	NFE 68603 E

Engin : Specs	
ACEA	E3
API	CG-4, CF-4, CE/SF
MB	227.1
CCMC	D4
Military	MIL-L-2104D

Specific Gravity @ 15.6°C	0.881
Kinematic Viscosity @ 40°C (cSt)	62
Kinematic Viscosity @ 100°C (cSt)	9.70
Flash Point COC (°C)	223
VI (Viscosity Index)	141
Pour Point °C	-38
TBN (mg KOH / g)	10.37

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfuels.co.uk>