

SUTO (Super Universal Tractor Oil) 15W-30

Product Description:

Lubricants Direct SUTO 15W-30 is a Super Universal Tractor Oil grade suitable for engines, transmissions, hydraulics and final drives. The latest agricultural machinery in the modern intensive farming environment needs the protection of a high quality lubricant. SUTO 15W30 is blended from carefully selected base oils and the latest in additive technology to produce a lubricant for the demands of most farm equipment. The latest additives used help reduce wet brake noise. The carefully selected base oils ensure protection even under the most arduous of conditions.

Benefits:

□

- Meets a range of OEM requirements
- Helps reduce wet brake noise or “squawk” □
- Suitable for many agricultural machinery requirements □ API diesel & petrol engine specifications

Application:

SUTO 15W-30 is suitable for use in both normally aspirated and turbocharged diesel and petrol

Specific Gravity @ 15.6°C	0.883
Kinematic Viscosity @ 40°C (cSt)	85.04
Kinematic Viscosity @ 100°C (cSt)	11.49
VI (Viscosity Index)	125
Flash Point COC (°C)	218
Pour Point (°C)	-31
TBN (mg KOH / g)	10.38

API	(Engine) SF/CE (Trans) GL-4
Caterpillar	TO-2
CCMC	D4/G2
Ford	M2C86A, 134B/C, 159B
MB	227.1
ZF	TE ML 06B, 06L, 07B, 07D
Allision	C-4
Massey Ferguson	M1135, 1127, 1139
John Deere	J20A

engines, transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives. It is suitable for agricultural, plant and off road machinery.

recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfuels.co.uk>