

## Slideway MP

### Product Description:

Lubricant Direct Slideway MP is a versatile range of multi-purpose lubricants achieving the high performance levels usually associated with mono-functional oils. Suitable for use in gears, bearings, slideways and hydraulic systems.

### Benefits:

- Excellent filterability
- Stick-slip prevention
- Good oxidation resistance
- Wide temperature range usage
- Good corrosion protection
- Excellent demulsibility
- Multi-functional applications

### Application:

Recommended for a wide variety of machine lubrication requirements. In particular, Slideway MP grades are highly effective machine tool slideway lubricants and demonstrate excellent performance in hydraulic, industrial gear and bearing applications.

### Typical Test Data:

ISO Grade	32	46	68	100	150	220	320	460	680
Density @ 15.5°C	0.872	0.875	0.880	0.883	0.890	0.895	0.899	0.903	0.907
Kinematic Viscosity @ 40°C (cSt)	32	46	68	100	150	220	320	460	680
Kinematic Viscosity @ 100°C (cSt)	5.3	6.8	8.5	11.2	14.5	19.1	24.2	31.2	34.4
Viscosity Index	98	97	97	97	96	96	96	96	96
Pour Point (°C)	-30	-30	-30	-30	-30	-28	-28	-26	-24
Flash Point (°C)	215	224	234	246	255	260	275	298	299

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfueoils.co.uk>