

Slideway Oils

Product Description:

Premium quality lubricating oils with added tacky and anti-fling additives for the lubrication of the slides on machine tools. The tackifier improves adhesion and prevents the oil from being squeezed off the slideways. It also helps prevent the oil from being washed away by cutting fluids, Slideway Oils also incorporate a mild EP additive.

Benefits:

- Excellent filterability
- Thermally stable
- Good oxidation resistance
- Wide temperature range usage
- Good corrosion protection
- Excellent demulsibility

Application:

Use for lubrication of slideways where smooth, stick-slip-free performance is required or where a tacky adhesive lubricant is required.

Typical Test Data:

ISO Grade	32	46	68	100	150	220	320	460	680
Density @ 15.5°C	0.849	0.852	0.857	0.879	0.895	0.898	0.901	0.911	0.900
Kinematic Viscosity @ 40°C (cSt)	32	46	68	100	150	220	320	460	680
Kinematic Viscosity @ 100°C (cSt)	6.1	7.8	8.3	8.9	13.5	17.9	23.5	31.4	35
Viscosity Index	150	150	151	151	154	156	156	158	160
Pour Point (°C)	-30	-30	-30	-30	-30	-28	-28	-26	-24
Flash Point (°C)	245	245	245	245	250	250	255	260	265

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfueoils.co.uk>