

Two Stroke Oil

Product Description:

Lubricants Direct Two Stroke Oil is a high quality, low ash two stroke oil. It has been specially formulated from the latest additive technology and base oil components to produce a low smoke, clean burning product. It is designed to exceed the performance requirements of API TC and is suitable for both premix and injector systems.

Suitable for the following:

Benefits:

□

- Protects against piston and cylinder scuffing
- Superior levels of anti-wear protection
- High lubricating film strength
- Greatly reduced deposit formation

API	TC
ISO	EGB
JASO	FB

Application:

Two Stroke Oil is suitable for use in motorcycles of low to medium output and can be used in a variety of two stroke applications such as chainsaws, hedge cutters, go karts, lawnmowers and snowmobiles.

Appearance	Red
Specific Gravity @ 15.6°C	0.880
Kinematic Viscosity @ 100°C (cSt)	8.94
Flash Point (COC °C)	170

Always refer to the equipment handbook for mixing ratios and specification requirements.

In line with our policy of continued improvement, Lubricants Direct reserve the right to change specification and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. A safety data sheet in conformity with the legislation now current in the EC is available from <http://www.fordfueloils.co.uk>